

Technical Specifications

Model S6280AP	DT128A
Processor & Speed	3.0HT GHz/800 Intel® Pentium® 4(P) Processor – PGA478
Chipset	Intel® 865G
Motherboard	Cobra-GL6E (4PSD-LA)
RAM	512/3200 MB 400DDR SDRAM (2x256)
Maximum	4 GB (4x1024MB DDR SDRAM)
Sockets	Four 184-pin DDR DIMMs
Size	128, 256, 512 AND 1024 MB DDR DIMMs
Free DIMM Sockets	Two
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	16KB Data Cache + Trace Cache L1, 1MB L2 Integrated on Processor module
Hard Drive	160 GB (7200 RPM)
Optical Drive – 1	DVD-ROM Drive: DVD (16x max.) / CD-ROM (48x max.)
Access Speed	DVD =115ms / CD-ROM =95ms
Transfer Rate	DVD = 21.6/sec. / CD-ROM = 7.2MB/sec.
Optical Drive – 2	CD-RW Drive: 48x-Write / 24X-Re-write/CD-ROM speed =48x max.
Access Speed	110ms
Transfer Speed	6.0MB/sec.
Diskette Drive	3.5" (1.44MB)
Video Graphics	AGP 8X Graphics Card
Controller	ATI R9200
Video Memory	128 MB DDR, not upgradeable
Video Connectors	Composite & S-Video – NTSC
Network Card	10/100 BaseT, Integrated
1394 Card	IEEE-1394, Integrated
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650
Chassis	Chameleon, 250HV PSU
USB Interface Specification	USB 2.0
External Ports	6= USB, 1= serial, 1= parallel, 2=1394
Front I/O Connector	2= USB, 1= 1394; 1= Microphone; 1=Headphone
Expansion Slots (Total)	3= PCI, 1= AGP
Expansion Slots (FREE)	3= PCI
Drive Bays (Total)	Two 5.25" external, One 3.5" external, Two 3.5" internal
Drive Bays (FREE)	One 3.5" external, One 3.5" internal
Keyboard/Mouse	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse

Copyright Hewlett-Packard Co. 1994-2003
This information is subject to change without notice and
is provided "as is" with no warranty.
Hewlett-Packard shall not be liable for any direct,
indirect, special, incidental or consequential damages
in connection with the use of this material.